












## Filling Connections

Filling connections for SCBA and diving cylinders in accordance with national/international standards.

	Gas	Description	Max WP	M16x1.5 mm for HP hose/lever filling valve	G1/4" for Oxygen hose	G1/4" for lever filling valves (-2005)	M16 x 1.5mm for cross filling valves	8 x 2.5 mm for piping connection
	Air	DIN 477 200 bar	232 bar / 3400 psi	●	●	●	●	●
	Air	DIN 477 200 bar anti whip	232 bar / 3400 psi	●	●			
	Air	DIN 477 300 bar	300 bar / 4500 psi	●		●	●	●
	Air	DIN 477 300 bar anti whip	300 bar / 4500 psi	●				
	Air	DIN 477 300 bar 360° swivel connection	300 bar / 4500 psi	●				
	Air	INT/Yoke for scuba	232 bar / 3400 psi	●	●		●	
	Air	CGA 346	200 bar / 3000 psi	●		●	●	
	Air	CGA 347	300 bar / 4000 psi	●		●	●	
	Air	NF E 29-662	232 bar / 3400 psi	●		●	●	
	Air	NF E 29-662 anti whip	232 bar / 3400 psi	●				
	Air	NF E 29-663	300 bar / 4500 psi	●		●	●	●
	Air	NF E 29-663 anti whip	300 bar / 4500 psi	●				
	Air	Spasciani	200 bar / 3000 psi	●				
	Nitrox	Draeger M24 x 2.0 prEN144	200 bar / 3000 psi		●			
	Nitrox	M26 x 2.0 - 250 bar	250 bar / 3675 psi		●			
	Nitrox	M26 x 2.0 - 350 bar	350 bar / 5000 psi		●			
	O <sub>2</sub>	G3/4" DIN 477	200 bar / 3000 psi		●			

If you need any other connections, please do not hesitate to ask.