

JONWAI

琮偉機械廠

SEW series



www.jonwai.com

SEW SPECIFICATION 機型規格

MODELS		JW-120SEW	JW-180SEW	JW-220SEW	JW-250SEW	JW-300SEW	機型
CLAMPING UNIT							鎖模系統
CLAMPING FORCE	ton	120	180	220	250	300	閉模力
PLATEN SIZE(H*V)	mm	720*620	830*730	890*790	1020*870	1130*950	模板大小
TIE -BAR DIS. (H*V)	mm	510*410	580*480	620*520	730*580	810*630	支柱內距
MOLD HEIGHT(MIN-MAX)	mm	150~550	150~650	150~700	250~760	250~900	模厚
OPEN DAYLIGHT	mm	510~760	600~1000	650~1050	800~1200	900~1350	模厚調整
HYDRA. EJECTOR STROKE	mm	100	130	150	160	180	托模行程

INJECTION UNIT		i12e			i18e			i22e			i25e			i30e			射出系統
SCREW DIAMETER	mm	38	42	45	50	55	60	55	60	65	60	65	70	65	70	75	螺桿直徑
INJECTION CAPACITY	cm ³	192	235	270	471	570	678	617	735	862	791	929	1077	1028	1193	1369	理論射出容積
SHOT SIZE(PS)	gr	170	208	238	416	503	599	546	649	730	699	821	952	908	1054	1210	射出重量
INJECTION PRESSURE(MAX)	kg/cm ²	2402	1966	1713	2394	1978	1662	2428	2040	1738	2288	1949	1681	2173	1873	1632	射出壓力
INJECTION RATE	cm ³ /sec	112	137	157	185	223	266	223	265	311	237	278	323	311	361	415	射出率



OFFICE

11F-3, NO. 30, SEC.3, CHUNG SHAN N. ROAD,
TAIPEI, TAIWAN
台北市中山區中山北路三段30號11樓之三
TEL:886-2-2595-4867

TAINAN FACTORY

NO. 5, TAYING. TAYING VILLAGE, HSIN-SHIN
SHIANG, TAINAN, TAIWAN.
台南市新市區大營5號
TEL:886-6-599-9321

QR CODE



infor.tw@jonwai.com.tw

www.jonwai.com

2016-07-R1