

NEW!

LW 450 ES III



Discover the new LW 450 ES III. Robust, dynamic and powerful.

The soundproofed compressor is suitable for demanding breathing air and high pressure applications and convinces with very low maintenance intervals and service costs. The industry-proven, new lubrication system, as well as reinforced compressor components are the main points of the optimized compressor block and improve sustainably the lifetime of the compressor. The innovative condensate system with the new condensate stop valve optimizes the economic efficiency of the compressor and includes a 10 liter condensate collecting tank as well as a highly effective pre-separator to extend the filter life.

The third generation of the ES series is suitable for use in workshops as well as mixed industrial buildings. The compressor is delivered full wired, ready for connection with automatic shut-off, automatic condensate drain and star/delta start cycle.



Figure with option 4-fold filling panel

NEW - Heavy duty compressor block components

NEW - Improved lubrication system c/w oil filter

NEW!

LW 450 ES III



Specifications

- » Electro motor (E-Motor / 400V / 3 Phase / 50 Hz)
- » Powder coated steel housing (RAL 6026)
- » Sound insulated housing
- » **NEW** - Heavy duty compressor block components
- » Automatic condensate drain
- » Automatic stop at final pressure
- » Hour counter
- » Operating panel with start/stop and condensate test button, as well emergency stop switch
- » Phase monitoring c/w shut down at wrong direction of rotation
- » Motor protection switch
- » Safety switch
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » 3 x concentric suction/pressure valves
- » **NEW** - Improved lubrication system c/w oil filter
- » Low pressure oil pump and filter
- » Oil- / Water separators in stainless steel
- » Safety valves after each stage
- » 0.8 ltr. Prefilter (Enlarged the lifetime of the filter by approx. 5 h)
- » Condensate-Stop-Valve
- » 10 Litre Condensate tank with venting silencer
- » Maintenance door on both sides
- » High pressure outlet with 1500 mm hose
- » Filling pressure of your choice (200 or 300 bar)
- » Breathing air purification an accordance to EN 12021

Options

- » Auto start system
- » Up to 6 additional hoses available
- » **NEU** - 4- fold filling panel installed at front door
- » 200 and 300 bar parallel filling pressures
- » Oil pressure gauge
- » Intermediate pressure gauges
- » Oil pressure monitoring c/w auto shut down
- » Cylinder head temperature monitoring with auto shut down
- » Oil temperature display with auto shut down
- » 2.3 ltr. Filter housing (Filter capacity: 1440 m³ at +20°C)
- » Puracon filter monitoring (Auto shut down also available)
- » Remote Tab Control - RTC
- » Power cable and plug
- » Special voltages / frequencies on request

Technical Data

LW 450 ES III	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm ³ /h] / [cfm]:	450 / 27.0 / 15.9
Max. Pressure [bar]:	350
RPM [1/min]:	1100
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor / 400V / 3 Phase / 50 Hz
Drive power [kW] with 50 Hz / 60 Hz:	11.0 / 13.2
Cooling air req. [m ³ /h] with 50 Hz / 60 Hz:	3300 / 3960
Lubrication type:	Oil pump
Oil capacity [litre]:	2.7
Oil pressure [bar]:	1.5 (+/- 0.2)
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m ³ at +20°C] ¹⁾ :	1050 (at +20°C / approx. 38 h)
Dimensions W x D x H [mm]:	975 x 1260 x 1800
Weight [kg]:	452
Noise level (measured at 1 m) [dB(A)]:	72 (+/- 2)

¹⁾ In accordance with EN 12021



เครื่องอัดอากาศ LW
by JST Engineering
LW compressors
Authorized agent
in Thailand

ศูนย์บริการลูกค้า
ทั่วประเทศ

JST ENGINEERING CO.,LTD.

78/6 MOO 7 KINGKAEW RD., RACHATEWA,
BANGPLEE, SAMUTPRAKARN 10540 THAILAND.

ศูนย์จระเข้ 081-684-0565
ศูนย์ดอนพูน 098-825-8600
ศูนย์จันทบุรี 092-247-6565



Facebook Page

☎ +66 (0) 2738 5050-4 🌐 URL: www.jst.co.th
☎ +66 (0) 2738 5055 📠 LINE ID: atthepjst
✉ info@jst.co.th 🌐 www.facebook.com/LWCompressor