

Puracon Stationary ECO



Puracon Stationary ECO

The usage of a Puracon monitoring system is the most reliable and economic method of breathing air monitoring. L&W Puracon systems can be ordered as an option for a new compressor unit or can also be easily integrated into an existing filling stations.

Puracon Stationary ECO is a cost-efficient solution for humidity monitoring during the filling procedure. The Puracon Stationary ECO can be connected directly to the high-pressure line after the humidity filter. The humidity value can be observed during the entire filling procedure. Exceeding of the limits will be indicated by a red LED.

Specifications

- » Adjustable measuring speed
- » Auto shut down (battery saving mode)
- » Pressure compensation
- » Higher accuracy by new temperature compensation
- » Storage of max. humidity value
- » Alarm LED - freely adjustable limit



Technical Data

Technical Data	Puracon Stationary ECO
Operating pressure	150 to 350 bar - adjustable pressure range
Power supply	2 x AAA LR03 alk. battery
Connector	G1/4 thread
Protection rating	IP64
Operating temperature	+5°C to +45°C
Dimensions	60 x 90 x 40 mm

เครื่องวัดความชื้น L&W
by JST Engineering
L&W compressors
Authorized agent
in Thailand

#เครื่องวัดความชื้น
หัวใจเครื่องอัด

JST ENGINEERING CO.,LTD.
78/6 MOO 7 KINGKAEW RD., RACHATEWA,
BANGPLEE, SAMUTPRAKARN 10540 THAILAND.

คุณวิโรจน์ 081-684-0565
คุณอดิเทพ 098-825-8600
คุณจักรภัทร 092-247-6565



Facebook Page

☎ +66 (0) 2738 5050-4 🌐 URL: www.jst.co.th
☎ +66 (0) 2738 5055 📠 LINE ID: atthepjst

✉ info@jst.co.th 📄 www.facebook.com/LWCompressor